

PA853W

Professional Installation Projector

Datasheet



The NEC PA853W - the “multi-tool” installation projector

If extraordinary visualisation, brilliant colours and superb dynamic contrast is key for your business, then the NEC PA853W should be your first choice.

The compact 8,500 ANSI lumen LCD projector with WXGA resolution not only trumps the competition with its unique colour processing technology, but also in its outstanding installation capabilities where motorized lens shift, focus and zoom makes setup effortless. The unique HDBaseT-out interface enables multiple projector daisy chaining via cost efficient network cables to a single source helping to reduce installation costs. Like a multi-tool, the essential features continue with management of the latest copyright protocol to play 4k and Ultra HD Blu-ray content whilst the long lamp life and even longer filter life earn a most attractive Total Cost of Ownership.

All in all the NEC PA853W projector is perfectly suited for meeting-, lecture- and seminar-rooms in corporate and higher education installations.

To reduce your installation costs, the projectors can be ordered bundled with the NP13ZL standard lens, which meets the projection requirements of 90% of all installations!

Bundle order code: 40001122

Benefits

Cinema Quality Visualisation - enjoy excellent picture quality even in bright ambient light conditions with unique picture & colour processing technology (up to up to 4K/60Hz) based on the latest NEC scaler chip.

Hassle-free remote adjustment - motorized lens shift, focus and zoom allows easy and flexible setup without the need for cumbersome physical access to the projector.

Incredible visualisation capabilities - impressive free tilt and portrait installation capability, unique geometric adjustment, picture in picture, tiling, 3D support and camera based blending/stacking up to 4K.

Cost conscious & powerful cabling - with just CAT6 network cabling, transfer content over up to 100m using HDBaseT connectivity standard. Supply multiple projectors with one source and benefit from the unique HDBaseT-out daisy-chain interface.

Impress with brilliant colours & contrast - astound your audience as the projector processes a wider colour space with Rec2020 to Rec709 colour conversion and higher dynamic contrast supporting HDR10 standard via HDMI interface.

Peace of mind copyright protected content - let the projector manage copyright protection and present 4k and Ultra HD Blu-ray content via the HDMI interface.

Product Information

Product Name	PA853W
Product Group	Professional Installation Projector
Order Code	60004119

Image

Projection Technology	3LCD Technology
Native Resolution	1280 x 800 (WXGA)
Aspect Ratio	16:10
Contrast Ratio ¹	10000:1
Brightness ¹	8500 ANSI Lumen (approx. 80% in Eco Mode), with std. optional lense
Lamp	420 W UHP AC (280 W UHP AC Eco Mode)
Lamp Life [hrs]	3000 (5000 Eco Mode)
Lens	3 motorized lens options; 5 manual lens options
Lense Adjustment	Motorized and manual (depending on lens)
Keystone correction	+/- 40° manual horizontal / +/- 40° manual vertical
Projection Factor	depending on lens selection (std. option NP41ZL at 1.3-3.02:1)
Projection Distance [m]	0.7 - 50.9
Screen Size (diagonal) [cm] / [inch]	(best performance range); Maximum: 1,270 / 500"
Zoom	Motorized and manual (depending on lens)
Focus Adjustment	Motorized and manual (depending on lens)
Supported Resolutions	4096 x 2160 (4k); 1920x1200 (WUXGA) 720p/60; 480p/60; 2560 x 1600 (WQXGA); - 640x480 (VGA); 720p/50; 480i/50 1080i/50/60; 576i/50; 2048 x 1080 (2k); 1080p/24/25/30/50/ 576p/50; 60;
Frequency	Horizontal: analog: 15/24-100 kHz, digital: 15/24-153 kHz; Vertical: analog: 48-120 Hz, digital: 48-120 Hz

Connectivity

RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr)
Digital	Input: 1 x DisplayPort; 1 x HDBaseT; 2 x HDMI™ supporting HDCP 2.2 Output: 1 x HDBaseT supporting HDCP 2.2
Audio	Input: 1 x DisplayPort Audio support; 1 x HDBaseT audio support; 2 x 3.5 mm Stereo Mini Jack for Computer analog; 2 x HDMI audio support Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Control	Input: 1 x 3.5 mm Stereo Mini Jack (Wired Remote); 1 x D-Sub 9 pin (RS-232), Ethernet
LAN	1 x RJ45
USB	1 x Type A (USB 2.0 high speed)
3D Sync	Output: 1 x Mini DIN 3pin

Remote Control

Remote Control	3D Setup; Aspect Ratio; Audio Control; Auto Adjust; DisplayPort; Eco Mode Control; Edge-Blending; Freeze-function; Geometric Correction; HDMI; Help-function; Magnify-function; Multiscreen; Page (up, down); PBP/POP Function; Picture Adjust; Picture Mute; PIP Function; Power (On-OFF); Select (up, down, left, right); Source Select; Test Picture
----------------	---

Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	542 (Normal) / 376 (Eco) / 1 (Network Stand-by) / 0.26 (Stand-by)

Mechanical

Dimensions (W x H x D) [mm]	499 x 163.7 x 406 (without lens and feet)
Weight [kg]	10.2
Fan Noise [dB (A)]	33 / 39 (Eco / Normal)

Environmental Conditions

Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80 non-condensing
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80 non-condensing

Ergonomics

Safety and Ergonomics	CE; EAC; ErP; RoHS; TUEV Type Approved
-----------------------	--

Additional Features

Special Characteristics	4K/60Hz interfaces; Active 3D; AMX Beacon; Built-in Display/Multiscreen Splitter; Cinema Quality Picture (CQP) Processing for best image quality; Contrast Ratio 10000:0 with Iris; Crestron RoomView; DICOM Simulation; Digital 3D Reform™; Direct Power-Off Function; Edge Blending Function; Free Tilt; Geometric Correction; HDBaseT-out signal connection; HDR10 Support; High Altitude Mode; Hollywood Quality Video Processing for best image quality; HTTP Browser Control; Keystone Correction (H=±40°, V=±40°); LAN control; Lens Memory; Lens Shift (vertical +0.5 max/-0.1 max, horizontal ± 0.3 max.); Light Source Adjustment; Long Life Lamp; Manual Wall Color Correction; Multi-Screen compensation mode; NaViSet Administrator 2; Optional User Logo; OSD with 27 languages; Password Security System; PIP/Side by Side, HDMI - Input; PJ LINK; Portrait Setting; Rec2020 to Rec709 colour conversion; RS-232 Control; Seamless Switching; Stacking Function; Test Pattern; Timer-Function; UHD player support; Up to 5,000 hrs lamp life; Virtual Remote for direct PC control
-------------------------	---

Green Features

Energy Efficiency	ECO scheduler; Intelligent Power Management; Less than 0.3W Stand-By power; Longer lamp life; Software scheduling; Timer-Function
Ecological Materials	100% recyclable packaging; Downloadable manuals
Ecological Standards	ErP compliant

Warranty

Projectors	3 years pan-European service
Light Source	6 months, max. 1000 hrs

Shipping Content

Shipping Contents	IR Remote Control (RD - 466E); Power Cord; Projector; Quick Setup Guide; Users Manual on CD-ROM
-------------------	---

Optional Accessories

Optional Accessories	8 optional bayonet lenses; Air Filter (NP06FT); Cable Cover (NP10CV); Ceiling Mount Kit; Lamp (NP42LP); MultiPresenter Stick; XpanD 3D Glasses (X105-RF-X2); XpanD 3D RF Emitter (AD025-RF-X2)
Lenses - motorized	NP40ZL (0.79-1.11:1); NP41ZL (1.3-3.02:1); NP43ZL (2.99-5.93:1); NP44ML (0.32:1)
Lenses - manual	NP11FL (0.81:1); NP12ZL (1.19-1.52:1); NP13ZL (1.46-2.95:1); NP14ZL (2.9-4.68:1); NP30ZL (0.79-1.04:1)

¹ Compliance with ISO21118-2012



TUEV Type
Approved



CE



ErP



RoHS

This document is © 2019 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 16.09.2019