

...the goal of all gesture is to study  
figure and see how it moves...

The human body is very complex,  
and gesture attempts to simplify the  
figure in the most possible.

## The gesture

...of the action, form, and pose of a model. Typical  
gestures involve an artist drawing a series of poses  
of a model in a short amount of time



NEC Display Solutions

# Large Format Displays

\Orchestrating a brighter world

**NEC**

## E Series | Entry Level Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Haze Level*	Orientation**	Input
<b>E327</b>	32 / 81	350	S	L	3 HDMI, VGA
<b>E437Q</b> <sup>1</sup>	43 / 109	350	S	L	3 HDMI, VGA
<b>E507Q</b> <sup>1</sup>	50 / 127	350	S	L	3 HDMI, VGA
<b>E557Q</b> <sup>1</sup>	55 / 140	350	S	L	3 HDMI, VGA
<b>E657Q</b> <sup>1</sup>	65 / 165	350	S	L	3 HDMI, VGA

167<sup>1</sup> 4K UHD 

- Slim design and integrated speakers
- Future-ready connectivity
- Standalone operation



## C Series | Value Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Haze Level*	Orientation**	Input
<b>C431</b>	43 / 109	400	P	L, P, FU	3 HDMI, DP, VGA
<b>C501</b>	50 / 127	400	P	L, P, FU	3 HDMI, DP, VGA
<b>C551</b>	55 / 140	400	P	L, P, FU	3 HDMI, DP, VGA
<b>C651Q</b> <sup>1</sup>	65 / 165	350	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
<b>C751Q</b> <sup>1</sup>	75 / 189	350	P	L, P	3 HDMI, DP: 2 In, 1 Out
<b>C861Q</b> <sup>1</sup>	86 / 217	350	P	L, P	3 HDMI, DP: 2 In, 1 Out
<b>C981Q</b> <sup>1</sup>	98 / 248	350	P	L, P	3 HDMI, DP: 2 In, 1 Out

247<sup>1</sup> 4K UHD 

- Integrated Media Player
- Slim profile and modern design for seamless integration
- Low reflective panel and “pixel-free” viewing experience for excellent readability<sup>1</sup>
- ShadowSense™ touch models available



## V Series | Value Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Haze Level*	Orientation**	Input
<b>V323-3</b>	32 / 81	450	S	L, P	HDMI, DP, DVI-D In/Out, VGA
<b>V404</b> <sup>2</sup>	40 / 102	500	P	L, P, FU, FD	2 HDMI, DP: 2 In, 1 Out, DVI-D, VGA
<b>V484</b> <sup>2</sup>	48 / 122	500	P	L, P, FU, FD	
<b>V554</b> <sup>2</sup>	55 / 140	500	P	L, P, FU, FD	
<b>V554Q</b> <sup>1,2</sup>	55 / 140	500	P	L, P	3 HDMI, DP: 2 In, 1 Out
<b>V654Q</b> <sup>1,2</sup>	65 / 165	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
<b>V754Q</b> <sup>1,2</sup>	75 / 189	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
<b>V864Q</b> <sup>1,2</sup>	86 / 217	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
<b>V984Q</b> <sup>1,2</sup>	98 / 248	500	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out

24/7

<sup>1</sup> 4K UHD



<sup>2</sup> SpectraView™ engine

- Open Modular Intelligence for scalable computing power
- Reliable colour reproduction
- “Pixel-free” viewing experience<sup>1</sup>
- 3M™ PCAP touch models available



## P Series | Professional Signage

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Haze Level*	Orientation**	Input
<b>P404</b>	40 / 102	700	P	L, P, FU, FD	2 HDMI, DP: 2 In, 1 Out, DVI-D, VGA
<b>P484</b>	48 / 122	700	P	L, P, FU, FD	
<b>P554</b>	55 / 140	700	P	L, P, FU, FD	
<b>P654Q</b> <sup>1</sup>	65 / 165	700	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out
<b>P754Q</b> <sup>1</sup>	75 / 189	650	P	L, P, FU	3 HDMI, DP: 2 In, 1 Out

24/7

<sup>1</sup> 4K UHD



SpectraView™ engine

- Open Modular Intelligence for scalable computing power
- Superb readability in bright light environments
- Long-term operation in demanding environments
- ShadowSense™ touch models available



## CB Series | Entry Level Collaboration

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Touch Technology	Orientation**	Front USB
<b>CB651Q</b>	65 / 164	350	Infrared	L	2
<b>CB751Q</b>	75 / 189	350	Infrared	L	2
<b>CB861Q</b>	86 / 217	350	Infrared	L	2



- Simple operation with front access to major functionalities
- Easy installation with included wallmount
- Instant start-up with built-in whiteboard and wireless screen sharing



## NEC InfinityBoards | Collaboration Solutions

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Touch Technology	Orientation**	USB Hubs
<b>55" InfinityBoard <sup>1</sup></b>	55 / 140	500	InGlass™	L, P, FU	4x USB 3
<b>65" InfinityBoard</b>	65 / 165	500	InGlass™	L, P, FU	4x USB 3
<b>75" InfinityBoard</b>	75 / 191	500	InGlass™	L, P, FU	4x USB 3
<b>86" InfinityBoard</b>	86 / 217	500	InGlass™	L, P, FU	4x USB 3

<sup>1</sup> only 2.1 model



- Create, collaborate, communicate
- Natural writing experience
- Simplified video conferencing
- 2.0 models with Huddly GO camera
- 2.1 models with Huddly IQ camera



# UN | UX Series | Video Wall Displays

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Haze Level <sup>1</sup>	Orientation <sup>2</sup>	Input
<b>UN462A</b> <sup>2,3</sup>	46 / 117	700	P	L, P	HDMI In/Out, DP In/Out, DVI-D, VGA
<b>UN462VA</b> <sup>2,3</sup>	46 / 117	500	P	L, P	
<b>UN492S</b> <sup>1,3</sup>	49 / 123	700	P	L, P	
<b>UN492VS</b> <sup>1,3</sup>	49 / 123	500	P	L, P	
<b>UN552A</b> <sup>2,3</sup>	55 / 140	700	P	L, P	
<b>UN552</b> <sup>1,3</sup>	55 / 140	700	P	L, P	
<b>UN552V</b> <sup>1,3</sup>	55 / 140	500	P	L, P	
<b>UN552S</b> <sup>1,3</sup>	55 / 140	700	P	L, P	
<b>UN552VS</b> <sup>1,3</sup>	55 / 140	500	P	L, P	
<b>X554UNS-2</b> <sup>2</sup>	55 / 140	700	P	L, P	DVI-D, HDMI, DP In/Out, VGA
<b>X554UNV-2</b> <sup>2</sup>	55 / 140	500	P	L, P	
<b>X555UNS</b> <sup>1</sup>	55 / 140	700	P	L, P	
<b>UN551S</b> <sup>1</sup>	55 / 140	700	P	L, P	
<b>UN551VS</b> <sup>1</sup>	55 / 140	500	P	L, P	
<b>UX552</b> <sup>2,3</sup>	55 / 140	700	P	L, P	HDMI In/Out, DP In/Out, DVI-D, VGA
<b>UX552S</b> <sup>2,3</sup>	55 / 140	700	P	L, P	

**24/7** **1080P**  
FULLHD IMAGE



**3** **SpectraView™**  
engine

Panel Technology IPS<sup>1</sup> or PVA<sup>2</sup>

- Enhanced imaging performance via the SpectraView™ engine
- Easy set-up with Auto TileMatrix
- Secure reliability and longevity
- UX Series supports connection of additional power supply for redundancy



## XHB Series | High Brightness

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Haze Level*	Orientation**	Input
<b>X554HB</b>	55 / 140	2700	S	L, P	HDMI, DP In/Out, DVI-D, VGA
<b>X754HB</b>	75 / 191	2500	S	L, P	

**24/7** **1080P**  
FULLHD IMAGE



- Programmable Ambient Light Sensor
- Sunlight-proof operation
- Automated thermal management



\* Haze Level (Anti-reflection): S=Standard (<5 %); A=Advanced (5 % - 25 %); P=Pro (>25 %)

\*\* Orientation: L=Landscape; P=Portrait; FU=Face Up; FD=Face Down

## BT Series | Stretched Display

---

MultiSync® Model	Size inch/cm	Brightness in cd/m <sup>2</sup>	Haze Level*	Orientation**	Input
<b>BT421</b>	42 / 107	700	Pro (44)	L, P	DVI: 2 In, 1 Out, LAN



- Space efficient display solution with ultra-wide screen ratio of 16:4

## NaViSet Administrator 2

---



Unified remote management software for NEC desktop monitors, large format displays and projectors.

## SpectraView Engine

---



Advanced settings of all relevant visual parameters allow full control of brightness, colour, gamma and uniformity via the SpectraView Engine for precise, natural images.

## Open Modular Intelligence (OMi)

---

Future ready expansion to upgrade the power of your display at any time by seamlessly integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute module 3 or signal interfaces for content feed and computing.

## Customisable Displays

---

Guaranteed reliability even under the toughest conditions is achieved with robust protective glass designed to withstanding external impacts. Available for NEC MultiSync® C / V / P / UN Series.

NEC MultiSync® P Series displays can be transformed into highly attractive and engaging devices with semi-transparent mirror glass.

Colour match NEC MultiSync® V and P Series displays to suit their environment with coloured bezels in any colour of the RAL range.

Document Name:	Large Format Displays Pocket Guide
Document Revision:	Edition 5, 2019
Document Date:	09/19
Created by:	FG

For more information visit us at  
[www.nec-display-solutions.com](http://www.nec-display-solutions.com)